




# Florian Schulz

## Ova

### Version

- brass burnished lacquered
- brass dark burnished lacquered
- brass matt brushed lacquered
- brass polished lacquered
- brass polished unlacquered
- chrome-plated brass
- copper-plated brass lacquered
- copper-plated brass matt brushed lacquered
- nickel-plated brass
- brass nickel-plated lacquered
- brass nickel-plated matt brushed

### Technical details

<b>Country of Manufacture</b>	 Germany
<b>Manufacturer</b>	Florian Schulz
<b>Designer</b>	Jens Schump
<b>Year of design</b>	2017
<b>protection</b>	IP20
<b>Scope of delivery</b>	LED
<b>material</b>	brass
<b>height adjustment</b>	height determinable
<b>dimming</b>	on site dimmable with a trailing edge dimmer
<b>Wattage</b>	96 W
<b>LED</b>	inclusive
<b>Colour Rendering Index</b>	>95
<b>Color temperature in Kelvin</b>	2,700 extra warm white
<b>canopy dimensions</b>	Width 47 cm, height 5 cm
<b>Total luminous flux in lm</b>	4,800
<b>light distribution</b>	directly and indirectly
<b>total height</b>	100 - 200 cm
<b>Dimensions</b>	H 4 cm   B 47 cm   L 125 cm

### Description

The VS Manufaktur Ova is a pendant lamp with an oval lamp body. The length of the lamp is 125 cm, it has a width of 47 cm. The lamp body is 4 cm high. The light is emitted both upwards and downwards. The Florian Schulz Ova is variably determinable in a height of 100 cm to 200 cm. On request, variants with different suspensions are also offered. An LED with a diffuser as well as an power of 60 watts and 2,700 Kelvin extra warm white is integrated. The pendant lamp is available in different surfaces: brass polished lacquered, nickel-plated, matt brushed lacquered, nickel-plated matt brushed, burnished lacquered, dark burnished lacquered, copper-plated, nickel-plated lacquered, polished unlacquered, copper-plated matt brushed lacquered as well as chrome-plated. On request, the pendant lamp is also available with a colour temperature of 3,000 Kelvin warm white or 4,000 Kelvin white. Only the pendant lamp with 230-240 volts can be dimmed on site. The 110 - 125 volt version is supplied here as a non-dimmable version.