




Mawa

Wittenberg 4.0 ceiling lamp Downlight LED

Oberfläche

- black
- white

Technical details

Country of Manufacture	 Germany
Manufacturer	Mawa
Designer	Jan Dinnebier
Designer 2	mawa engineering
protection	IP20
Scope of delivery	LED
Diameter in cm	8
material	aluminum, metal
beam angle	38 degrees
dimming	dimmable with a trailing edge dimmer and with a leading edge dimmer
Wattage	12.7 W
LED	inclusive
Colour Rendering Index	95
Luminous flux in lm	1,100
Color temperature in Kelvin	2,700 extra warm white
bulb exchange	on site itself
light distribution	directly
Dimensions	H 12 cm Ø 8 cm

Description

The Mawa Wittenberg 4.0 ceiling lamp Downlight LED emits its light directly and bundled downwards. Neither screws nor cables are visible in the compact design of the lamp. This lamp has a height of 11.5 cm and a diameter of 7.6 cm. An LED is integrated as a light source, which can be dimmed by the customer with a leading or trailing edge phase dimmer. On request, the lamp is also available as a DALI or 1-10 volt dimmable version. These two optionally available versions (DALI or 1-10 Volt) then have a height of 14.7 cm with a diameter of 7.6 cm. The Wittenberg 4.0 ceiling lamp Downlight LED is available with powder-coated black matt or white matt surfaces. The integrated LED has a colour temperature of 2,700 Kelvin extra warm white. On request it is also offered with 3,000 Kelvin warm white or 4,000 Kelvin white.

The radiator has a beam angle of 38 degrees. The beam angle determines the angle at which the light from an LED spotlight is emitted. With a larger beam angle, the light is distributed over a larger area. Optionally, the lamp can also be ordered with a beam angle of 12 or 24 degrees in the field Order Comment.