



Cini & Nils

Acqua 3 lamps with round canopy

Oberfläche

- gold
- silver
- white

Version

- Downlight
- Uplight

Technical details

Country of Manufacture	 Italy
Manufacturer	Cini & Nils
Designer	Luta Bettonica
Year of design	2014
protection	IP20
Scope of delivery	LED
material	aluminum, steel
height adjustment	height determinable
dimming	with built-in dimmer controlled by a switch
LED	inclusive
Colour Rendering Index	95
Color temperature in Kelvin	2,800 warm white
canopy dimensions	16 cm
system performance	3 x 5.6 Watt
Total luminous flux in lm	1,950
total height	200 cm
Dimensions	H 86 cm B 10 cm L 11 cm

Description

The Cini & Nils Acqua 3 lamps with round canopy consists of three lamps. The three lights are plugged together and suspended jointly from the round canopy. The lamp is available in the surfaces white, silver matt and gold matt. On request it is also offered in silver leaf or gold leaf. The canopy with a diameter of 16 cm is delivered in the matching surface to the lamp. The Acqua is available in two versions: As an uplight it emits indirect light directed upwards and as a downlight it emits direct light downwards.

The pendant light is regulated with a switch-controlled, integrated dimmer. This means that the light can be dimmed continuously via the normal light switch. No additional cables are required. The dimming function is activated by switching on and off once. The maximum light intensity is reached within seven seconds. To save the desired light intensity, switch on and off again. The set light intensity is saved via a memory function and is automatically selected when the lamp is switched on again. On request, the lamp can also be supplied with a push dimmer on site.

In addition to this Acqua with 3 lights on a round canopy, versions with up to 6 lights are also available on request. The lamp is also available on request with an oval canopy with up to ten lights. The Acqua pendant light can be adjusted in height if required. A decentralisation kit is offered as an accessory, which allows the lamp to be installed independently of a power supply.