



less'n'more

Athene Wall / Ceiling Light A-BDL2

Dimmbarkeit

- Push button dimmer at the canopy
- on site dimmable with a trailing edge dimmer

Oberfläche

- aluminum
- black
- white

flexible_arm

- textile blue
- textile anthracite
- aluminum
- textile green
- textile red
- textile brown
- textile white
- textile black

Technical details

Country of Manufacture	 Germany
Manufacturer	less'n'more
Designer	less'n'more
protection	IP43
Scope of delivery	LED
material	aluminum, glass
beam angle	25 - 100 degrees
Wattage	4.8 W
LED	inclusive
Colour Rendering Index	90
Luminous flux in lm	600
Color temperature in Kelvin	2,700 extra warm white
canopy dimensions	7 cm
light head dimensions	7 cm
bulb exchange	on site itself
Dimensions	L max. 62 cm

Description

The Less'n'more Athene Wall / Ceiling Light A-BDL2 is mounted on the ceiling or wall. The surface-mounted lamp has a flexible lamp arm that can be stretched and bent as desired. At maximum extension of the lamp arm, the wall and ceiling lamp has a total length of 62 cm. The flexible lamp arm is offered in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown. An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated in the aluminum lamp head. The canopy / wall mount made of aluminum has a diameter of 6.5 cm.

The lamp head and the canopy are available in the surfaces aluminum and black. The Athene Wall / Ceiling Lamp A-BDL2 is offered dimmable on site with a trailing edge phase dimmer or with an integrated push button dimmer on the canopy. The version with push button dimmer can be switched and dimmed via the push button. At the lamp head, the beam angle of the light can be continuously adjusted between 25 and 100 degrees. To do this, simply turn the glass lens out of or into the lamp head. With a larger beam angle, the light is distributed over a larger area.

Besides this Athene wall and ceiling lamp, a smaller lamp of this series with a maximum length of 31 cm is also available, the Athene Wall / Ceiling Light A-BDL1. On request, the lamp is also offered with other colours for the flexible lamp arm or with a protective contact plug for operation at a power socket. A canopy mounting plate is offered as an accessory, with which the lamp can be mounted over a flush-mounted box.