




# Gera Leuchten

## Pendant Lamp 40x40x900 RC

### Oberfläche

- aluminum
- stainless Steel
- black brown

### Technical details

<b>Country of Manufacture</b>	 Germany
<b>Manufacturer</b>	Gera Leuchten
<b>protection</b>	IP20
<b>Scope of delivery</b>	LED
<b>material</b>	aluminum
<b>height adjustment</b>	height determinable
<b>dimming</b>	with remote control
<b>Wattage</b>	17 W
<b>LED</b>	inclusive
<b>Luminous flux in lm</b>	1,260
<b>Color temperature in Kelvin</b>	2,700 - 4,000 adjustable
<b>bulb exchange</b>	on site itself
<b>total height</b>	20 - 250 cm
<b>Dimensions</b>	H 4 cm   B 4 cm   L 90 cm

### Description

The pendant lamp 40x40x900 RC by the German manufacturer Gera is operated with an integrated LED. This LED pendant lamp is available in the finishes aluminium-coloured and stainless steel-coloured. The pendant lamp made of aluminium is 90 cm long, 4 cm wide and 4 cm high. This elongated pendant lamp made of aluminium has a 58 cm long, 3.4 cm wide and 3.4 cm high ceiling suspension. The lamp connection is located directly at the connection terminal. The LED pendant lamp with square cross-section emits its light brightly and glare-free downwards. The LED low-voltage technology used in this lamp allows "cable-free" suspension from fine, current-conducting steel cables. The Gera Leuchten pendant lamp 40x40x900 RC is adjustable in total height from 20 cm to 250 cm.

This pendant lamp is supplied with a radio remote control. The lamp can be switched on and off via the existing light switch as well as via the remote control. The brightness of the lamp can also be regulated via the remote control. Even at full light output, the colour temperature can be adjusted from 2,700 Kelvin extra warm white to 4,000 Kelvin via the remote control supplied. The last settings selected are saved. If necessary, the integrated LED can be changed by the user. The Gera Leuchten pendant lamp 40x40x900 RC is also available in other lengths, as well as a version with sensor dimmer (touch-free switching and dimming).