



# Byok

## Piani Mono 165 Downlight


### Oberfläche

- Aluminium pulido
- aluminio mate
- negro mate

### Leuchte

- altura ajustable
- ajustable en altura

## Technical details

<b>País de la Fabricación</b>	 Alemania
<b>fabricante</b>	Byok
<b>diseñador</b>	Kai Byok
<b>protección</b>	IP20
<b>Volumen de suministro</b>	LED
<b>material</b>	aluminio
<b>longitud del cable</b>	300 cm
<b>Atenuación</b>	Regulable en el sitio con control de fase inversa
<b>LED</b>	incluyendo
<b>Indice de reproduccion cromatica</b>	>90
<b>Temperatura de color en grados Kelvin</b>	2.700 extra blanco cálido
<b>reemplazo de la bombilla:</b>	en el fabricante / en la fabrica
<b>El rendimiento del sistema</b>	10 x 3,6 Watt
<b>Flujo total luminoso en lm</b>	3.060
<b>Dimensiones</b>	H 1 cm   B 5 cm   L 165 cm

## Descripción

The Byok Piani Mono 165 Downlight is a pendant lamp. The lamp body of the Piani Mono 165 Downlight is milled out of massive aluminum and polished or eloxated by hand afterwards. Ten LEDs are dazzle-free installed due to reflector technics and they may be exchanged singly.

Three surfaces are on offer: aluminum matt, aluminum polished or black matt. This pendant lamp is offered height-determinable (the cables can be set to the desired length during assembly) or height-adjustable (the total height can also be adjusted after assembly). The integrated LEDs can be **dimmed on site with a trailing edge phase dimmer**. On request, they are also available with gesture control and Dim2Warm technology. With gesture control, the light is dimmed by holding the hand flat under the lamp. With Dim2Warm technology, the light takes on a warmer colour when dimmed. When dimmed, the light colour of the LEDs changes from 2,700 Kelvin extra warm white to 2,100 Kelvin extra warm white. The dimming range is between 0 and 100 percent.