



Cini & Nils

Passepartout 25

Version

- oro
- cromo
- negro
- blanco

Dimmbarkeit

- sensor dimmer
- Regulable en el sitio con control de fase inversa
- con módulo Casambi

Technical details

| | |
|--|--|
| País de la Fabricación |  Italia |
| fabricante | Cini & Nils |
| diseñador | Luta Bettonica |
| año | 2017 |
| protección | IP20 |
| Volumen de suministro | LED |
| Diámetro en cm | 25 |
| material | acero, aluminio |
| ajuste de altura | altura determinada |
| LED | incluyendo |
| Indice de reproduccion cromatica | 92 |
| Temperatura de color en grados Kelvin | 2.800 blanco cálido |
| Dimensiones del dosel | 16 cm |
| El rendimiento del sistema | 1 x 9 Watt Downlight + 2 x 5 Watt Uplight |
| Flujo total luminoso en lm | 2.200 |
| altura total | 250 cm |
| Dimensions | H 2 cm Ø 25 cm |

Descripción

The Cini & Nils Passepartout 25 pendant lamp emits light simultaneously upwards and downwards. The light is bundled in both directions by a lens. The lamp has a diameter of 25 cm and a height of 2.3 cm. The Passepartout 25 is available in four versions: white matt, black matt, chrome polished and gold polished. All versions except gold have a diamond-polished aluminum support element for the lens. The gold version has a matt brass support. The lamp itself is always made of steel.

The Passepartout 25 is offered in three dimmabilities: dimmable on site with a trailing edge phase dimmer, with an integrated Casambi module or with an integrated sensor dimmer. The version with Casambi module can be dimmed with the Casambi App via Bluetooth by a smartphone / tablet. The version with sensor dimmer is switched on and off by moving the hand under the sensor. The light is dimmed by holding the hand under the sensor. The total height is a maximum of 250 cm, the cables can be shortened if required. On request, an accessory is available with which two Passepartout lamps can be mounted on a common power connection.