


## Cini & Nils

### Convivio pendant lamp decentralized LED

#### Oberfläche

- cromo
- negro

#### Technical details

|  |  |
|--|--|
| <b>País de la Fabricación</b>                |  Italia |
| <b>fabricante</b>                            | Cini & Nils  |
| <b>diseñador</b>                             | Luta Bettonica   |
| <b>diseñador 2</b>                           | Mario Melocchi   |
| <b>año</b>                                   | 2005   |
| <b>protección</b>                            | IP20   |
| <b>Volumen de suministro</b>                 | LED  |
| <b>Diámetro en cm</b>                        | 11   |
| <b>material</b>                              | acero, aluminio, latón, vidrio   |
| <b>longitud del cable</b>                    | 385 cm   |
| <b>ajuste de altura</b>                      | altura determinada   |
| <b>Atenuación</b>                            | Regulable en el sitio con control de fase inversa  |
| <b>Potencia en vatios</b>                    | 13 W   |
| <b>LED</b>                                   | incluyendo   |
| <b>Indice de reproducción cromática</b>      | 92   |
| <b>El flujo luminoso en lm</b>               | 1.300  |
| <b>Temperatura de color en grados Kelvin</b> | 2.800 blanco cálido  |
| <b>Dimensiones del dosel</b>                 | 14 cm  |
| <b>Dimensions</b>                            | H 65 cm   Ø 11 cm  |

#### Descripción

The Cini & Nils Convivio pendant lamp decentralized LED has a transparent glass lens through which the light is bundled and emitted directly downwards. This transparent lens provides a distinctive, clear illumination. The lamp is supplied with a decentralized canopy, which allows it to be mounted independently of the power supply. The Convivio is available in chrome and matt black. The integrated LED is on site dimmable with a trailing edge phase dimmer. With an optionally available Casambi module, the light can also be dimmed with the Casambi App via Bluetooth using a smartphone / tablet. A version with integrated Casambi module is also offered on request. The maximum cable length of 385 cm can be individually set during assembly.