



Knapstein

HELLI-1


Oberfläche

- níquel
- negro
- bronce

Struktur

- Níquel
- negro
- bronce

Technical details

País de la Fabricación	 Alemania
fabricante	Knapstein
año	2023
Diámetro en cm	8
material	Acryl, Metall
ajuste de altura	altura ajustable
Atenuación	control por movimientos
Potencia en vatios	2x8 W
LED #	inclusive
Indice de reproduccion cromatica	>90
El flujo luminoso en lm	2140
Temperatura de color en grados Kelvin	2.700 blanco cálido extra
protección	IP20
Volumen de suministro	LED
dosel	Ø9cm
reemplazo de la bombilla:	en el fabricante / en la fabrica
altura total	70 - 170 cm
Dimensions	Ø 8 cm

Descripción

The Knapstein HELLI-1 LED pendant lamp has a cylindrical lamp body with freely combinable structures on the underside of the luminaire. The glass of the lower diffuser of the luminaire is reversible, making it easy to choose between a lens for a focussed lighting effect and a disc for a diffuse lighting effect. To do this, unscrew the lower light ring and place the enclosed glass in the desired position (lens/disc). The aforementioned screw ring (structure) is available in 3 different colours. A swiping hand movement in the sensor area switches the corresponding light source on or off. To dim the light, the hand is held in front of the respective sensor until the desired light intensity is reached. Thanks to the integrated memory function, the last settings are saved and are immediately available again the next time the light is switched on. The uplight and downlight can be switched and dimmed separately using gesture control. With the built-in lift height adjustment, the luminaire height can be continuously adjusted from approx. 70 cm - 170 cm. The Knapstein HELLI-1 has a synchronisation function for adjusting the light intensity of all light sources on one side of the luminaire. The ceiling canopy of the Knapstein HELLI-1 LED pendant lamp has a magnetic holder, so no external screw connections are visible. This pendant lamp is available in several surfaces and freely combinable external structures on the underside.