

less'n'more

Zeus Wall / Ceiling Light Z-BDL1

Dimmbarkeit

- Touchez Dimmer à la canopée
- dimmerable sur place avec commande gradateur de phase inverse

Oberfläche

- aluminium
- noir
- blanc

flexible arm

- vert Textile
- rouge Textile
- marron Textile
- blanc Textile
- noir Textile
- bleu textile
- anthracite Textile
- aluminium

Technical details

Pays de fabrication

fabricant

concepteur

protection

Contenu de la livraison

matériel

angle du faisceau

Puissance en Watt

LED

Indice de rendu des couleurs

Flux lumineux en lm

La température de couleur en Kelvin

canopée Dimensions

tête de luminaire masse

remplacement des ampoules :

Dimensions

Allemagne

less'n'more

less'n'more

IP43

LED

aluminium, verre

15 - 75 degres

4,2 W

y compris

90

450

2.700 extra blanc chaud

7 cm

3 cm

sur le site meme

L max. 30 cm

Description

The Less'n'more Zeus Wall / Ceiling Light Z-BDL1 can be mounted on the wall or ceiling. It is built onto the surface. Its canopy / wall mounting made of aluminum has a diameter of 6.5 cm. This lamp has a flexible lamp arm that can be stretched and bent as desired. At maximum extension of the lamp arm, the lamp has a length of 30 cm. The flexible lamp arm is offered in these colours: aluminum, textile black, white, anthracite, blue, green, red and brown. An LED with a colour temperature of 2,700 Kelvin extra warm white is integrated in the lamp head.

The lamp head and the canopy are available in the surfaces aluminum and black. The Zeus Wall / Ceiling Light Z-BDL1 is offered on site dimmable with a trailing edge phase dimmer or with an integrated push button dimmer on the canopy. The version with push button dimmer can be switched and dimmed via the push button. The beam angle of the light can be continuously adjusted between 15 and 75 degrees. To do this, the glass lens is turned out of or into the lamp head. With a larger beam angle, the light is distributed over a larger area.

On request, this Zeus wall and ceiling lamp is also available with other colours for the flexible lamp arm or with a supply cable and safety plug for operation at a power socket. A larger lamp with a maximum length of 62 cm is also offered from the series. A canopy mounting plate is offered as an accessory, with which the lamp can be mounted over a flush-mounted box.