



Mawa

Bullauge 6 pendant mounting with uplight

Durchmesser in cm

- 45
- 60
- 80
- 120

Technical details

Land van fabricage	 Duitsland
fabrikant	Mawa
ontwerper	Martin Wallroth
bescherming	IP20
Omvang van de levering	LED
materiaal	acrylglas, aluminium
kabellengte	250 cm
hoogteverstelling	hoogte bepaalbaar
dimmen	dimbaar met fase- en fase-afsnijding en fase-regelingsdimmer
LED	inclusief
lichtverdeling	direct en indirect
Dimensions	H 10 cm

Omschrijving

The Mawa Bullauge 6 pendant mounting with uplight emits light both upwards and downwards. The pendant light is available with a diameter of 45 cm, 60 cm, 80 cm or 120 cm. As standard, the lamp is made of aluminum in powder-coated white matt. On request it can also be supplied in other RAL colours. The even distribution of the LEDs and the opaque, satinised plexiglass diffuser ensure a very homogeneous, luminous surface at the bottom of the lamp. The three smaller versions of Bullauge 6 pendant mounting with uplight are suspended on three parallel cables, the largest lamp on four parallel cables. The cables have a maximum length of 250 cm and can be shortened if necessary. On request, the lamp is also available with other cable lengths or without uplight.

The Bullauge 6 can be dimmed with a leading edge or trailing edge phase dimmer. On request, it is also available DALI dimmable. It is also offered with a different diameter up to 120 cm on request. As standard, the three smaller lamps are supplied with a colour temperature of 2,700 Kelvin extra warm white, on request they are also available with 3,000 Kelvin warm white. The pendant lamp with a diameter of 120 cm has a colour temperature of 3,000 Kelvin warm white.