



# Catellani & Smith

## Syphasera Set 1

### Höhe in cm

- 65
- 80
- 110
- 140

### Technical details

|                                   |  |
|-----------------------------------|--|
| <b>Land van fabricage</b>         |  Italië |
| <b>fabrikant</b>                  | Catellani & Smith  |
| <b>ontwerper</b>                  | Enzo Catellani   |
| <b>jaar</b>                       | 2018   |
| <b>bescherming</b>                | IP44   |
| <b>Omvang van de levering</b>     | LED  |
| <b>materiaal</b>                  | messing, opaalglas   |
| <b>base/versie</b>                | G4   |
| <b>Wattage</b>                    | 1 W  |
| <b>LED</b>                        | inclusief  |
| <b>Kleurweergave-index</b>        | 80   |
| <b>Lichtstroom in lm</b>          | 75   |
| <b>Kleurtemperatuur in Kelvin</b> | 2.700 extra warm wit   |
| <b>bulb vervangen:</b>            | ter plaatse zelf   |

### Omschrijving

The Catellani & Smith Syphasera Set 1 consists of a complete, ready-to-connect outdoor floor lamp with all the necessary accessories. The set includes: a ground spike, an extension cable with a length of 500 cm and a driver required for operation. The connection cable for the power connection must be provided by the customer. The light has a cylindrical opal glass through which the light is emitted glare-free in all directions. With its ground spike, the light can be fixed up to 25 cm into the ground. The Syphasera Set 1 is available with a luminaire with a height of 65 cm, 80 cm, 110 cm or 140 cm (height without spike).

The Syphasera's light rod has an IP65 protection rating, making it dustproof and protected against strong water jets from any angle. The outdoor floor lamp itself is protected against splashing water on all sides and solid foreign bodies with a diameter of 1 mm or more with an IP44 protection rating. The driver and extension cable are protected against temporary submersion with an IP67 protection rating. Syphasera also offers other sets consisting of several complete, ready-to-connect lights.